




BMW E60 D1151 Front Ceramic Brake Pads 34116763652 ATE Braking System

Basic Information

. Place of Origin: China . Brand Name: OEM ISO9000 · Certification: ALL Model Number: • Minimum Order Quantity: 100 • Price: 5.00-25.00 · Packaging Details: export packing • Delivery Time: 30-60 • Payment Terms: T/T, LC



Product Specification

. Supply Ability:

Product Name:
BMW E60 Ceramic Brake Pad

15 Million

Model: BMW E60
Type: Brake Pad
Material: Ceramic
Factory No.: ZK-04006
F/R: F
FMSI: D1151
OEM: 34116763652

Braking System:
ATE

• Highlight: BMW E60 front ceramic brake pads,

E60 bmw oem brake pads,

34116763652 front ceramic brake pads

Product Description

Specifications	
Product name	BMW E60 Ceramic Brake Pad
Model	BMW E60
Туре	Brake Pad
Material	Ceramic
F/R	F
Factory No.	ZK-04006
FMSI	D1151
OEM	34116763652
Braking System	ATE
	Size
Width	193.2 mm
Height	79.2 mm
Thickness	19.6 mm
Model_MARKE	5 Series E60/E61 (03-04)/ 6 Series E63/E64 (2004)/ 7 Series E65/E66 (2001)

Optimized Performance with BMW E60 Ceramic Brake Pads (D1151, 34116763652)

Elevate your BMW E60's braking capabilities with our top-tier ceramic brake pads. Tailored specifically for the 2004-2010 BMW 5 Series models, these pads are engineered to provide unmatched stopping power with minimal dust and noise. The D1151 pad set, carrying the part number 34116763652, is designed for a perfect fit on your vehicle's front brakes, ensuring a seamless installation and immediate enhancement in braking performance.

Superior Stopping Power: Experience enhanced safety with reliable, high-performance braking.

Reduced Brake Dust: Keep your wheels cleaner with low-dust ceramic compounds.

Quiet Braking: Enjoy a noise-free ride thanks to advanced vibration-damping technology.

Direct Fit: Guaranteed compatibility with BMW E60 models for a straightforward replacement.

For the ultimate in braking precision and longevity, choose our BMW E60 ceramic brake pads.

Our ceramic brake pads, crafted from a specially formulated ceramic blend, showcase exceptional performance owing to their unique material composition.

The manufacturing process adheres to the rigorous standards of international certification IATF-16949, ensuring the utmost reliability in product quality.

Withstanding temperatures of up to 640°C, our ceramic brake pads offer a reliable safeguard for braking needs under diverse driving conditions.

Employing original high-precision molds and specialized heat treatment techniques, we guarantee the precision and stability of our products.

Addressing brake squeal concerns, our pads boast a friction coefficient of PS 0.35, coupled with heat resistance up to 640°C, maintaining outstanding braking performance even in high-temperature environments. This prolongs lifespan and effectively resolves brake squeal issues.

Prioritizing safety and comfort, our stable friction coefficient preserves brake disc integrity, while the comfortable pedal feel and low-noise design enhance driving pleasure and reduce environmental pollution.

Featuring unique chamfered edges, our pads not only reduce braking noise but also enhance compatibility with counterpart components, further elevating braking performance.

Exceptional heat dissipation performance is achieved through high-temperature and high-pressure burnishing, reducing bedding-in periods and minimizing noise occurrences, thereby enhancing pad cooling efficiency and ensuring braking stability

Designed for lightweight, our ceramic brake pads, compared to traditional metal ones, effectively reduce vehicle load, improving fuel economy and power performance.

Minimizing brake dust, our ceramic brake pads produce less dust compared to their metal counterparts, making them environmentally friendly and less intrusive to the cleanliness of the vehicle surroundings and wheels.

Quality assurance is paramount to us. Through stringent quality controls and continuous research and development efforts, we ensure the stability and reliability of each ceramic brake pad, earning the trust and acclaim of our users.









