China OEM

ISO9000


ALL



## Volvo S80L D1305 Front Ceramic Brake Pads 1405511 Ate Braking System

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100
- Price: 5.00-25.00
- Packaging Details: export packing
- Delivery Time: 30-60
- Payment Terms: T/T, LC
- Supply Ability: 15 Million



## **Product Specification**

<ul> <li>Product Name:</li> </ul>	Volvo S80L Ceramic Brake Pad
• Model:	Volvo S80L
• Type:	Brake Pad
<ul> <li>Material:</li> </ul>	Ceramic
<ul> <li>Factory No.:</li> </ul>	ZK-25007
• F/R:	F
• FMSI:	D1305
• OEM:	1405511
<ul> <li>Braking System:</li> </ul>	Ate
Highlight:	Volvo S80L front ceramic brake pads, 1405511 front ceramic brake pads, 1405511

Our Product Introduction

Specifications	
Product name	Volvo S80L Ceramic Brake Pad
Model	Volvo S80L
Туре	Brake Pad
Material	Ceramic
F/R	F
Factory No.	ZK-25007
FMSI	D1305
OEM	1405511
Braking System	Ate
	Size
Width	156.5 mm
Height	74.4 mm
Thickness	17.8 mm
Model_MARKE	Volvo (Changan) S80L (2009/03-)

The Ceramic Brake Pad D1305 for Volvo S80L is the ideal choice for those seeking exceptional braking performance. Made with superior ceramic materials, it ensures stability and durability under various driving conditions. Its unique noise-reducing shim design offers a quieter driving experience. With product code 1405511, it is compatible with the Volvo S80L, providing your vehicle with racecar-like precision in braking control.

Our ceramic brake pads, crafted from a specially formulated ceramic blend, showcase exceptional performance owing to their unique material composition.

The manufacturing process adheres to the rigorous standards of international certification IATF-16949, ensuring the utmost reliability in product quality.

Withstanding temperatures of up to 640°C, our ceramic brake pads offer a reliable safeguard for braking needs under diverse driving conditions.

Employing original high-precision molds and specialized heat treatment techniques, we guarantee the precision and stability of our products.

Addressing brake squeal concerns, our pads boast a friction coefficient of PS 0.35, coupled with heat resistance up to 640°C, maintaining outstanding braking performance even in high-temperature environments. This prolongs lifespan and effectively resolves brake squeal issues.

Prioritizing safety and comfort, our stable friction coefficient preserves brake disc integrity, while the comfortable pedal feel and low-noise design enhance driving pleasure and reduce environmental pollution.

Featuring unique chamfered edges, our pads not only reduce braking noise but also enhance compatibility with counterpart components, further elevating braking performance.

Exceptional heat dissipation performance is achieved through high-temperature and high-pressure burnishing, reducing bedding-in periods and minimizing noise occurrences, thereby enhancing pad cooling efficiency and ensuring braking stability and safety.

Designed for lightweight, our ceramic brake pads, compared to traditional metal ones, effectively reduce vehicle load, improving fuel economy and power performance.

Minimizing brake dust, our ceramic brake pads produce less dust compared to their metal counterparts, making them environmentally friendly and less intrusive to the cleanliness of the vehicle surroundings and wheels.

Quality assurance is paramount to us. Through stringent quality controls and continuous research and development efforts, we ensure the stability and reliability of each ceramic brake pad, earning the trust and acclaim of our users.

