China OEM

ISO9000

5.00-25.00

volume

export packing

Production according to customer demand

ALL



Cadillac 2010-2011 CTS Ceramic Brake Pad Front D1331, 25958115

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100
- Price:
 - Packaging Details:
 - Delivery Time:
 - Payment Terms: T/T, LC
 - Supply Ability:
- 30-60

Product Specification

Product Name:	Cadillac 2010-2011 CTS Ceramic Brake Pad
• Model:	Cadillac 2010-2011 CTS
• Type:	Brake Pad
• Material:	Ceramic
 Factory No.: 	ZK-16009
• F/R:	F
• FMSI:	D1331
• OEM:	25958115
 Braking System: 	Ν
• Highlight:	Cadillac 2010-2011 CTS ceramic brake pad, 25958115 ceramic brake pad, Cadillac ceramic brake pad

Specifications	
Product name	Cadillac 2010-2011 CTS Ceramic Brake Pad
Model	Cadillac 2010-2011 CTS
Туре	Brake Pad
Material	Ceramic
F/R	F
Factory No.	ZK-16009
FMSI	D1331
OEM	25958115
Braking System	Ν
Size	
Width	162.1mm
Height	69.7 mm
Thickness	16.3mm
Model_MARKE	Cadillac New SLS Hybrid

The Cadillac 2010-2011 CTS Ceramic Brake Pads, model D1331 with part number 25958115, are meticulously engineered for the front axle (F), delivering outstanding braking performance and enduring durability. Crafted from premium ceramic materials, these brake pads ensure smooth, quiet stops under various driving conditions. Their high-temperature stability and low wear rate make them a reliable choice, reducing maintenance costs and enhancing the vehicle's safety features. Our ceramic brake pads, crafted from a specially formulated ceramic blend, showcase exceptional performance owing to their unique material composition.

The manufacturing process adheres to the rigorous standards of international certification IATF-16949, ensuring the utmost reliability in product quality.

Withstanding temperatures of up to 640°C, our ceramic brake pads offer a reliable safeguard for braking needs under diverse driving conditions.

Employing original high-precision molds and specialized heat treatment techniques, we guarantee the precision and stability of our products.

Addressing brake squeal concerns, our pads boast a friction coefficient of PS 0.35, coupled with heat resistance up to 640°C, maintaining outstanding braking performance even in high-temperature environments. This prolongs lifespan and effectively resolves brake squeal issues.

Prioritizing safety and comfort, our stable friction coefficient preserves brake disc integrity, while the comfortable pedal feel and low-noise design enhance driving pleasure and reduce environmental pollution.

Featuring unique chamfered edges, our pads not only reduce braking noise but also enhance compatibility with counterpart components, further elevating braking performance.

Exceptional heat dissipation performance is achieved through high-temperature and high-pressure burnishing, reducing bedding-in periods and minimizing noise occurrences, thereby enhancing pad cooling efficiency and ensuring braking stability and safety.

Designed for lightweight, our ceramic brake pads, compared to traditional metal ones, effectively reduce vehicle load, improving fuel economy and power performance.

Minimizing brake dust, our ceramic brake pads produce less dust compared to their metal counterparts, making them environmentally friendly and less intrusive to the cleanliness of the vehicle surroundings and wheels.

Quality assurance is paramount to us. Through stringent quality controls and continuous research and development efforts, we ensure the stability and reliability of each ceramic brake pad, earning the trust and acclaim of our users.



202, Minxiang Road, Sibaoshan Private Science and Technology Industrial Park, High-tech Zone, Zibo City, Shandong Province, China