



D555 Audi A6 Front Brake Pads 4A0698151 Audi Oem Brake Pads

Basic Information

Place of Origin: China
Brand Name: OEM
Certification: ISO9000
Model Number: ALL
Minimum Order Quantity: 100
Price: 5.00-25.00
Packaging Details: export packing
Delivery Time: 30-60

Delivery Time: 30-60
Payment Terms: T/T, LC
Supply Ability: 15 Million



Product Specification

Model:

• Braking System:

Product Name: Audi A6 Ceramic Brake Pad

Audi A6

Type: Brake Pad
 Material: Ceramic
 Factory No.: ZK-02003
 F/R: F
 FMSI: D555
 OEM: 4A0698151

• Highlight: 4A0698151 audi oem brake pads,

4A0698151 audi a6 front brake pads,

Oem audi a6 brake pads

Product Description

	Specifications
Product name	Audi A6 Brake Pad
Model	Audi A6
Туре	Brake Pad
Material	Ceramic
F/R	F
Factory No.	ZK-02003
FMSI	D555
OEM	4A0698151
Braking System	ATE
	Size
Width	156.3 mm
Height	74 mm
Thickness	19.4 mm
Model_MARKE	Audi A6/ Old Audi V6/ Audi 5000

Superior Stopping Power with Audi A6 Ceramic Brake Pads

Elevate your driving experience with our D555 Ceramic Brake Pads, designed specifically for the Audi A6. These front axle pads are the perfect replacement for part number 4A0698151, ensuring a flawless fit and exceptional performance. **Key Features:**

Precision Engineered: Manufactured to OEM specifications for guaranteed compatibility with your Volkswagen Audi A6. **Ceramic Material:** Benefit from reduced brake dust and noise, providing a cleaner and guieter ride.

Optimal Performance: Enjoy consistent, responsive braking under various driving conditions.

Durability: Our brake pads are built to last, offering you peace of mind on every journey.

Whether you're navigating tight city corners or cruising on the highway, our Audi A6 Ceramic Brake Pads will help you stop on a dime, every time.

Our ceramic brake pads, crafted from a specially formulated ceramic blend, showcase exceptional performance owing to their unique material composition.

The manufacturing process adheres to the rigorous standards of international certification IATF-16949, ensuring the utmost reliability in product quality.

Withstanding temperatures of up to 640°C, our ceramic brake pads offer a reliable safeguard for braking needs under diverse driving conditions.

Employing original high-precision molds and specialized heat treatment techniques, we guarantee the precision and stability of our products.

Addressing brake squeal concerns, our pads boast a friction coefficient of PS 0.35 and heat resistance up to 640°C, maintaining outstanding braking performance even in high-temperature environments. This prolongs lifespan and effectively resolves brake squeal issues.

Prioritizing safety and comfort, our stable friction coefficient preserves brake disc integrity, while the comfortable pedal feel and low-noise design enhance driving pleasure and reduce environmental pollution.

Featuring unique chamfered edges, our pads not only reduce braking noise but also enhance compatibility with counterpart components, further elevating braking performance.

Exceptional heat dissipation performance is achieved through high-temperature and high-pressure burnishing, reducing bedding-in periods and minimizing noise occurrences, thereby enhancing pad cooling efficiency and ensuring braking stability and safety.

Designed for lightweight, our ceramic brake pads, compared to traditional metal ones, effectively reduce vehicle load, improving fuel economy and power performance.

Minimizing brake dust, our ceramic brake pads produce less dust compared to their metal counterparts, making them environmentally friendly and less intrusive to the cleanliness of the vehicle surroundings and wheels.

Quality assurance is paramount to us. Through stringent quality controls and continuous research and development efforts, we ensure the stability and reliability of each ceramic brake pad, earning the trust and acclaim of our users.

86-533-2906-358



ysun7393@gmail.com



brakepadsset.com

202, Minxiang Road, Sibaoshan Private Science and Technology Industrial Park, High-tech Zone, Zibo City, Shandong Province, China