China OEM

ISO9000

ALL



## D795 ATE Volvo S80 Rear Brake Pad Replacement 272399 rear brake pads

## **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 100
- Price: 5.00-25.00
- Packaging Details: export packing
- Delivery Time: 30-60
- Payment Terms: T/T, LC
- Supply Ability: 15 Million

## **Product Specification**

<ul> <li>Product Name:</li> </ul>	Volvo S80 Ceramic Brake Pad
Model:	Volvo S80
• Туре:	Brake Pad
Material:	Ceramic
<ul> <li>Factory No.:</li> </ul>	ZK-25002
• F/R:	R
• FMSI:	D795
• OEM:	272399
<ul> <li>Braking System:</li> </ul>	ATE
• Highlight:	ATE volvo s80 rear brake pad replacement, 272399 volvo s80 rear brake pad replacement, 272399 rear brake pads

Specifications	
Product name	Volvo S80 Brake Pad
Model	Volvo S80
Туре	Brake Pad
Material	Ceramic
F/R	F
Factory No.	ZK-25002
FMSI	D795
OEM	272399
Braking System	ATE
Size	
Width	122.6 mm
Height	53.8 mm
Thickness	16.1 mm
Model_MARKE	Volvo S80 (Import)/ Volvo S70/ Volvo V70

## Volvo S80 Ceramic Brake Pads - D795 Series

Enhance the braking efficiency of your Volvo S80 with our D795 series ceramic brake pads. These pads are designed to provide a superior braking experience, with a focus on reducing noise and dust. Ideal for Volvo S80 drivers who prioritize both performance and cleanliness.

**Product Features:** 

OEM Part Number: 272399, R

Material: Advanced ceramic compound for quieter and cleaner operation

Vehicle Fit: Custom-designed for the Volvo S80

**Design:** Crafted with precision for a seamless fit and easy installation

Performance: Offers excellent stopping power with minimal brake fade

Comfort: Low-noise formulation for a more pleasant driving experience

Our D795 ceramic brake pads are the perfect choice for your Volvo S80, providing you with a reliable and efficient braking system that keeps your wheels clean and your rides quiet.

Our ceramic brake pads, crafted from a specially formulated ceramic blend, showcase exceptional performance owing to their unique material composition.

The manufacturing process adheres to the rigorous standards of international certification IATF-16949, ensuring the utmost reliability in product quality.

Withstanding temperatures of up to 640°C, our ceramic brake pads offer a reliable safeguard for braking needs under diverse driving conditions.

Employing original high-precision molds and specialized heat treatment techniques, we guarantee the precision and stability of our products.

Addressing brake squeal concerns, our pads boast a friction coefficient of PS 0.35 and heat resistance up to 640°C, maintaining outstanding braking performance even in high-temperature environments. This prolongs lifespan and effectively resolves brake squeal issues.

Prioritizing safety and comfort, our stable friction coefficient preserves brake disc integrity, while the comfortable pedal feel and low-noise design enhance driving pleasure and reduce environmental pollution.

Featuring unique chamfered edges, our pads not only reduce braking noise but also enhance compatibility with counterpart components, further elevating braking performance.

Exceptional heat dissipation performance is achieved through high-temperature and high-pressure burnishing, reducing bedding-in periods and minimizing noise occurrences, thereby enhancing pad cooling efficiency and ensuring braking stability and safety.

Designed for lightweight, our ceramic brake pads, compared to traditional metal ones, effectively reduce vehicle load, improving fuel economy and power performance.

Minimizing brake dust, our ceramic brake pads produce less dust compared to their metal counterparts, making them environmentally friendly and less intrusive to the cleanliness of the vehicle surroundings and wheels.

Quality assurance is paramount to us. Through stringent quality controls and continuous research and development efforts, we ensure the stability and reliability of each ceramic brake pad, earning the trust and acclaim of our users.

